



D = 50mm H = 117mm

	Model	416105960 - PPM 450V 75MF+-5 50X117*/
1	Dielectric	Self-healing metallized polypropylene
2	Filling	Polyurethane resin
3	Case material	Thermoplastic self-extinguishing V2 class
4	Capacitance / Tolerance	75MF +/- 5%
5	Rated frequency	50 Hz – 60 Hz
6	Rated voltage	a) AC 400 V 45 μ F ÷ 60 μ F b) AC 425 V 2 μ F ÷ 40 μ F c) AC 450 V 45 μ F ÷ 60 μ F d) AC 475 V 2 μ F ÷ 40 μ F
7	Life expectancy	a-b) 10.000h / cl.B c-d) 3.000h / cl.C
8	Climatic category	25/85/21
9	Class of safety protection	S0
10	Test Voltage between terminals	2 U _N x 2"
11	Test Voltage between terminals to case	3 kV x 2"
12	Insulating Resistance between terminals	10 x 10 ³ M Ω x μ F
13	Tan δ	$\leq 20 \times 10^{-4}$ measured at the rated voltage, 50Hz, 20°C
14	dV/dt (max)	20 V/ μ s
15	Tested and Certified according to	EN 60252-1/A1
16	Certification marks	VDE-IMQ